

Overview

Fast make and break regardless of how pressure is applied or released. Rugged construction. Phosphor bronze, self cleaning contacts withstand shock and vibration. Insulated, protective sleeves.

Standard Features – 850 and 854 Series

- AC or DC up to 250 volts
- Quick make and break
- CSA certified

No. 850

Locknut type. Complete with 1/2" locknut. Flexible No. 16 gauge wire leads, 3" (76mm) long. Normally open contacts.

No. 854

Locknut type, closed contacts - Same as No. 850 except contacts are normally closed.

Standard Features – 820 and 821 Series

- Quick break
- CSA Certified

No. 820

Force Fit. For thin metal panel mounting see No. 821.

No. 821

Locknut type. Has modified 1/2" conduit locknut. Ideal for panel mounting. Also mounts in hole drilled 25/32" (20) and tapped with straight pipe threads.

Ordering Information

Cat. No.	Description	Contact Ratings			Hole Size inches (mm)	Hole Depth inches (mm)	Finish	
		Volts	AC Amps	DC Amps			Rim	Center
820	Force Fit N.O.	12	15.0	15.0	3/4 (19)	1-3/4 (44)	Heavy Duty Shell, Chrome Plated	Black
		24	15.0	10.0				
		48	10.0	5.0				
821	Locknut N.O.	125	5.0	1.0	7/8 (22)	1-3/4 (44)	Heavy Duty Shell, Chrome Plated	Black
		250	5.0	--				
850	Locknut N.O.	12	10.0	10.0	7/8 (22)	1-3/4 (44)	Heavy Duty Shell, Chrome Plated	Black
		24	10.0	10.0				
		32	10.0	8.0				
		48	10.0	7.0				
		125	6.0	3.0				
		250	3.0	1.0				
854	Locknut N.C.	12	4.0	4.0	7/8 (22)	1-3/4 (44)	Heavy Duty Shell, Chrome Plated	Black
		24	4.0	4.0				
		48	4.0	2.0				
		125	2.0	1.0				
		250	1.0	0.5				

High Voltage Pushbuttons

850, 854, 820 and 821 Series



850/854



820



821

